

MODEL 6215



DEEP ANTI-GLARE HOUSING KIT

10W – 40W | 15° / 24° / 36° / 60° Beam | Profile Aluminum
Anti-Glare Baffle | Dual Spring Clips | Profile Aluminum Heatsink

MODEL 6215

ENGINEERED FOR PERFORMANCE



SPECIFICATIONS

Model 6215 Series — Parameter Guide (14 size options)



No.	Wattage	Face Dia (mm)	Cutout (mm)	Height (mm)	Beam Angle	No.	Wattage	Face Dia (mm)	Cutout (mm)	Height (mm)	Beam Angle
1	10-12W	63	55	86	15°/24°/36°/60°	8	25-30W	92	80	140	15°/24°/36°/60°
2	15W	63	55	110	15°/24°/36°/60°	9	10-12W	97	90	83	15°/24°/36°/60°
3	10-12W	83	75	83	15°/24°/36°/60°	10	15-20W	97	90	110	15°/24°/36°/60°
4	15-20W	83	75	110	15°/24°/36°/60°	11	25-30W	97	90	140	15°/24°/36°/60°
5	25-30W	83	75	140	15°/24°/36°/60°	12	30-35W	108	95	124	15°/24°/36°/60°
6	10-12W	92	80	83	15°/24°/36°/60°	13	35-40W	108	95	145	15°/24°/36°/60°
7	15-20W	92	80	110	15°/24°/36°/60°	14	30W	108	95	125	15°/24°/36°/60°

Housing kit only — driver and light source not included.

MODEL 6215

DIMENSIONS



Face Diameter

63 – 108 mm

Ceiling Cutout

55 – 95 mm

Overall Height

83 – 145 mm

MODEL 6215

MODULAR HOUSING KIT

Kit Contents: Housing · Optical Lens · Spring Clips

- Profile Aluminum Housing & Heatsink
- Anti-Glare Optical Lens
(15° / 24° / 36° / 60°)
- Stainless Steel Spring Clips
- Anti-Glare Cup:
White / Black / Gun Metal / Bright Silver



MODEL 6215

PARTS LINE-UP

Kit Contents: Housing · Optical Lens · Spring Clips



1. Heatsink Base

2. LED Holder

3. Inner Ring

4. Optical Lens

5. Housing Frame

6. Spring Clips



ABOUT US & CONTACT

ECO LED Kit — Your Strategic Lighting Housing Partner

Since 2018, ECO LED Kit has specialized in housing kits for LED downlights and spotlights. OEM / ODM welcome.

WhatsApp / WeChat: +86 132 4938 9989

E-mail: sales@ecoledkit.com

amylai1239@163.com

Website: www.ecoledkit.com

Contact: Ms. Amy Lai

Zhongshan Hongxin Pinyue Lighting Co., Ltd.

No. 16, Xiangxian 1st Street, Sansha, Henglan Town,

Zhongshan, Guangdong, China